

Opening Doors Around the World® www.gliderol.co.uk







Space Saving

Rolls up vertically and does not swing out in front of the garage. You can park right up to the door and have more storage space in the roof of the garage.

Easy to Operate

Easy to open and close with minimum noise and friction giving reliable performance at all times.

Security

Unique profile and aluminium bottom rail reinforce our roller doors against intruder penetration.



Minimal Maintenance

No oiling or greasing, just an occasional clean of the guides with white spirit and the door surface with warm soapy water.

Weatherseal

Durable bottomseal on the underside of the door prevents leaves and other undesirable materials entering your garage from outside.

Locking

The double-sided locking system is operated from the central handle and locks from both the inside and outside of the door. No lock is supplied on automatic doors.

Gliderol Roller Door Mini available for garages with limited headroom.



Easy to Use



1986 - 2016

Glidermatic remote control allows the door to be opened or closed either by means of a compact hand transmitter or by a wall mounted control box in the garage. Either way, the door opens and closes smoothly and quietly.

Security

The risk of another handset using the same code is eliminated as the transmitter uses a different code from one of two billion after every operation.



Safety

The door reverses automatically should the downward movement of the door be restricted.

Quiet Operation

Noise is reduced as the motor is housed entirely within the roll of the door giving a quiet and smooth performance.

Automatic Light

Lights your garage for up to 90 seconds after the motor is activated allowing you to drive into an illuminated garage.





All Gliderol products are CE marked (newly re-tested) and manufactured within our audited ISO 9001 quality systems (recently updated to 2015)

External Manual Release/ Dual Override Key Switch (Optional Extra)

If your garage has no other entry point an external manual release allows access in case of power failure. This is a simple key switch which connects via a cable to pin on the side of the motor and upon pulling will disengage the motor to allow manual operation of the door.





Gliderol Roller Door Mini



The Mini Roller is a compact version

that requires reduced space above the door opening - perfect for flat roof garages or other space restricted garages. The door is available up to 2100mm high and 3400mm wide in all the same finishes and with the option of automation.



Raising Standards Safety Assured



All Gliderol products are CE marked (newly re-tested) and manufactured within our audited ISO 9001 quality systems (recently updated to 2015)



Sizes - Up to 5 metres wide and 3 metres high (up to 4.9 metres for B-series – ask for details). Requires no frame so enables the maximum possible opening width for the wider vehicle. Door sits behind the brickwork so can be fitted in arched and unusual garage door openings.

Windlock system - should be specified for double doors in very exposed locations and greater side room clearance is required. For advice and information, speak to our technical department or your supplier.

Converting to automatic - whilst manual doors can be easily converted to automatic later, there is a significant cost saving if the unit is factory-fitted at the outset.



Guarantees - so long as the door is correctly installed and reasonably maintained, 2 years electrical, 6 years mechanical and 10 years on the door finish. CE tested and approved. Ask for details.

Presented by: